

**FAG****20217-K-MB-C3** [↗](#)

Barrel roller bearing

Barrel roller bearing 202..-K-MB

## Technical information

**Main Dimensions & Performance Data**

d	85 mm	Bore diameter
D	150 mm	Outside diameter
B	28 mm	Width
$C_r$	155.000 N	Basic dynamic load rating, radial
$C_{0r}$	201.000 N	Basic static load rating, radial
$C_{ur}$	20.800 N	Fatigue load limit, radial
$n_G$	4.750 1/min	Limiting speed
$\approx m$	2,14 kg	Weight

**Mounting dimensions**

$d_{a \min}$	96 mm	Minimum diameter shaft shoulder
$D_{a \max}$	139 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2 mm	Maximum recess radius
$d_{a \max}$	102 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	90 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	6 mm	Minimum cavity width of the sleeve

**Dimensions**

$r_{\min}$	2 mm	Minimum chamfer dimension
$D_1$	133,9 mm	Bore diameter outer ring

**Temperature range**

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

**Additional information**

H217	Adapter sleeve
------	----------------