

**FAG****20220-K-MB-C3** [↗](#)

Barrel roller bearing

Barrel roller bearing 202..-K-MB

Technical information

**Main Dimensions & Performance Data**

d	100 mm	Bore diameter
D	180 mm	Outside diameter
B	34 mm	Width
C_r	225.000 N	Basic dynamic load rating, radial
C_{0r}	290.000 N	Basic static load rating, radial
C_{ur}	28.500 N	Fatigue load limit, radial
n_G	4.000 1/min	Limiting speed
$\approx m$	3,81 kg	Weight

Mounting dimensions

$d_{a \min}$	112 mm	Minimum diameter shaft shoulder
$D_{a \max}$	168 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,1 mm	Maximum recess radius
$d_{a \max}$	120 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	106 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	7 mm	Minimum cavity width of the sleeve

Dimensions

r_{\min}	2,1 mm	Minimum chamfer dimension
D_1	160,8 mm	Bore diameter outer ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Additional information

H220	Adapter sleeve
------	----------------