**FAG****2211-K-TVH-C3**

Self-aligning ball bearing

Self-aligning ball bearing 22..-K-TVH,
tapered bore taper 1:12, plastic cage

Technical information

**Main Dimensions & Performance Data**

d	55 mm	Bore diameter
D	100 mm	Outside diameter
B	25 mm	Width
C_r	39.000 N	Basic dynamic load rating, radial
C_{0r}	12.500 N	Basic static load rating, radial
C_{ur}	790 N	Fatigue load limit, radial
n_G	7.000 1/min	Limiting speed
n_{gr}	6.700 1/min	Reference speed
$\approx m$	0,727 kg	Weight

Mounting dimensions

$d_{a \min}$	64 mm	Minimum diameter shaft shoulder
$d_{a \max}$	68 mm	Maximum diameter shaft shoulder
$D_{a \max}$	91 mm	Maximum diameter of housing shoulder
$d_{b \min}$	60 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	10 mm	Minimum cavity width of the sleeve
$r_{a \max}$	1,5 mm	Maximum fillet radius

Dimensions

r_{\min}	1,5 mm	Minimum chamfer dimension
D_1	89,8 mm	Shoulder diameter outer ring
d_1	69,64 mm	Shoulder diameter inner ring

Temperature range


T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.



View product details on medias

25.04.2024, 17:16:55 CEST

SCHAEFFLER



Calculation factors

e	0,22	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	2,91	Dynamic axial load factor
Y_2	4,51	Dynamic axial load factor
Y_0	3,05	Static axial load factor

Additional information

H311	Adapter sleeve
------	----------------