


**3803-2Z**

Angular contact ball bearing

Angular contact ball bearing 38.-B-2RZ-TVH, double row, shields, plastic cage

Technical information

**Main Dimensions & Performance Data**

d	17 mm	Bore diameter
D	26 mm	Outside diameter
B	7 mm	Width
C_r	2.430 N	Basic dynamic load rating, radial
C_{0r}	2.020 N	Basic static load rating, radial
C_{ur}	108 N	Fatigue load limit, radial
n_G	23.000 1/min	Limiting speed
n_{gr}	13.200 1/min	Reference speed
$\approx m$	0,013 kg	Weight

Mounting dimensions

$d_{a \min}$	19 mm	Minimum diameter shaft shoulder
$D_{a \max}$	24 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,3 mm	Maximum fillet radius

Dimensions

r_{\min}	0,3 mm	Minimum chamfer dimension
D_1	22,96 mm	Shoulder diameter outer ring
D_2	23,86 mm	Caliber diameter outer ring
d_1	20,3 mm	Shoulder diameter inner ring
d_2	19,24 mm	Caliber diameter inner ring
a	12,3 mm	Distance between the apexes of the pressure cones
α	25 °	Contact angle

Temperature range

T_{\min}	-20 °C	Operating temperature min.
T_{\max}	100 °C	Operating temperature max.

