


**3814-2Z**

Angular contact ball bearing



Angular contact ball bearing 38.-B-2RZ-TVH, double row, shields, plastic cage

Technical information



Main Dimensions & Performance Data

d	70 mm	Bore diameter
D	90 mm	Outside diameter
B	15 mm	Width
C_r	18.800 N	Basic dynamic load rating, radial
C_{0r}	23.200 N	Basic static load rating, radial
C_{ur}	1.310 N	Fatigue load limit, radial
n_G	5.700 1/min	Limiting speed
n_{gr}	4.050 1/min	Reference speed
$\approx m$	0,205 kg	Weight

Mounting dimensions

$d_{a \min}$	73,2 mm	Minimum diameter shaft shoulder
$D_{a \max}$	86,8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,6 mm	Maximum fillet radius

Dimensions

r_{\min}	0,6 mm	Minimum chamfer dimension
D_1	84,48 mm	Shoulder diameter outer ring
D_2	86,32 mm	Caliber diameter outer ring
d_1	77,7 mm	Shoulder diameter inner ring
d_2	76,48 mm	Caliber diameter inner ring
a	43,6 mm	Distance between the apexes of the pressure cones
α	25 °	Contact angle

Temperature range

T_{\min}	-20 °C	Operating temperature min.
T_{\max}	100 °C	Operating temperature max.

