

**FAG****52324-MP**

Axial deep groove ball bearing

Axial deep groove ball bearing 523..-MP,
double direction, solid brass cage

Technical information

**Main Dimensions & Performance Data**

d	100 mm	Inner diameter shaft washer
D	210 mm	Outer diameter housing washer
T ₂	123 mm	Height
C _a	325.000 N	Basic dynamic load rating, axial
C _{0a}	910.000 N	Basic static load rating, axial
C _{ua}	32.500 N	Fatigue load limit, axial
n _G	1.610 1/min	Limiting speed
n _{gr}	3.100 1/min	Reference speed
≈m	19,344 kg	Weight

Mounting dimensions

d _{a max}	120 mm	Maximum diameter shaft shoulder
D _{a max}	156 mm	Maximum diameter of housing shoulder
r _{a max}	2,1 mm	Maximum filled radius
r _{a1 max}	1 mm	Maximum filled radius

Dimensions

D ₁	123 mm	Inner diameter housing washer
B	27 mm	Height shaft washer
r _{min}	2,1 mm	Minimum chamfer dimension
r _{1 min}	1,1 mm	Minimum chamfer dimension

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Calculation factors

A	4,4	Minimum load factor
---	-----	---------------------