


FAG


# 53312 🖸


# Axial deep groove ball bearing

Axial deep groove ball bearing 533, single direction, with spherical housing washer, steel sheet metal cage

#### Technical information







#### Main Dimensions & Performance Data

d	60 mm	Inner diameter shaft washer
D	110 mm	Outer diameter housing washer
Т	38,3 mm	Height
C <sub>a</sub>	101.000 N	Basic dynamic load rating, axial
C <sub>0a</sub>	207.000 N	Basic static load rating, axial
C <sub>ua</sub>	9.500 N	Fatigue load limit, axial
n <sub>G</sub>	3.150 1/min	Limiting speed
n <sub>9r</sub>	5.700 1/min	Reference speed
≈m	1,372 kg	Weight

### **Mounting dimensions**

d <sub>a min</sub>	90 mm	Minimum diameter shaft shoulder
D <sub>a max</sub>	85 mm	Maximum diameter of housing shoulder
r <sub>a max</sub>	1 mm	Maximum filled radius

#### Dimensions

r <sub>min</sub>	1,1 mm	Minimum chamfer dimension
D <sub>1</sub>	62 mm	Inner diameter housing washer
d <sub>1</sub>	110 mm	Outer diameter shaft washer
R	90 mm	Radius spherical housing washer
Α	41 mm	Distance of the center point
T <sub>1</sub>	42 mm	Height with seat washer

## Temperature range


T <sub>min</sub>	-30 °C	Operating temperature min.
T <sub>max</sub>	150 °C	Operating temperature max.

# Calculation factors

Α	0.28	Minimum load factor	







#### **Additional information**

U312

Seat washer