




## 71808-TN

Angular contact ball bearing

Schaeffler ID:  
0096210240000

Angular contact ball bearing 718.-B-TVP,  
single row, plastic cage

### Technical information



### Main Dimensions & Performance Data

d	40 mm	Bore diameter
D	52 mm	Outside diameter
B	7 mm	Width
$C_r$	6.300 N	Basic dynamic load rating, radial
$C_{0r}$	5.800 N	Basic static load rating, radial
$C_{ur}$	405 N	Fatigue load limit, radial
$n_G$	16.200 1/min	Limiting speed
$n_{gr}$	7.200 1/min	Reference speed
$\approx m$	0,033 kg	Weight

### Mounting dimensions

$d_{a \min}$	42 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	50 mm	Maximum diameter of housing shoulder
$D_{b \max}$	50,6 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,3 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	0,2 mm	Maximum fillet radius of housing

### Dimensions

$r_{\min}$	0,3 mm	Minimum chamfer dimension
$r_{1 \min}$	0,2 mm	Minimum chamfer dimension
$D_1$	47,3 mm	Shoulder diameter on outer ring wide side face
$d_1$	44,7 mm	Shoulder diameter on inner ring wide side face
a	22,8 mm	Distance between the apexes of the pressure cones
$\alpha$	40 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

