


FAG

HS71918-E-T-P4S-UL

Angular contact ball bearing

Spindle bearings HS719..-E, adjusted, in pairs or sets, contact angle $\alpha = 15^\circ$, restricted tolerances

Technical information



Main Dimensions & Performance Data



d	90 mm	Bore diameter
D	125 mm	Outside diameter
B	18 mm	Width
C_r	21.900 N	Basic dynamic load rating, radial
C_{0r}	17.700 N	Basic static load rating, radial
C_{ur}	1.810 N	Fatigue load limit, radial
$n_{G \text{ Grease}}$	13.000 1/min	Limiting speed for grease lubrication
$n_{G \text{ Oil}}$	20.000 1/min	Limiting speed for oil lubrication
$\approx m$	0,62 kg	Weight

Mounting dimensions

d_a	97 mm	Diameter shaft shoulder
d_a	h12	Diameter shaft shoulder clearance
D_a	119 mm	Shoulder diameter outer ring
D_a	H12	Shoulder diameter outer ring clearance
$r_{a \text{ max}}$	0,6 mm	Maximum recess radius
$r_{a1 \text{ max}}$	0,6 mm	Maximum recess radius
$E_{tk \text{ min}}$	103,2 mm	Minimum diameter injection pitch
$E_{tk \text{ max}}$	104,8 mm	Maximum diameter injection pitch
$E_{tk1 \text{ min}}$	100,6 mm	Minimum diameter injection pitch
$E_{tk1 \text{ max}}$	104,8 mm	Maximum diameter injection pitch
a	34,1 mm	Distance between the apexes of the pressure cones

Dimensions

r_{min}	1,1 mm	Minimum chamfer dimension
$r_{1 \text{ min}}$	1,1 mm	Minimum chamfer dimension
α	25 °	Contact angle





Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	100 °C	Operating temperature max.

Additional information

F_{VL}	129 N	Preload force light
F_{VM}	386 N	Preload force medium
F_{VH}	773 N	Preload force heavy
K_{aEL}	371 N	Lift-off force light
K_{aEM}	1.133 N	Lift-off force medium
K_{aEH}	2.309 N	Lift-off force heavy
c_{aL}	144 N/ μm	Axial rigidity light
c_{aM}	214 N/ μm	Axial rigidity medium
c_{aH}	279 N/ μm	Axial rigidity heavy